



Formulated For The Professionals  
Adhesives & Sealants

# VT-652 High Performance MS Sealant

## Advanced MS Polymer

VT-652 High Performance MS Sealant is a high modulus sealant based on advanced MS Polymer technology. It is a single-component sealant with superior weathering, UV, and temperature resistance. It also gives good primer-less adhesion on most substrates. Unlike polyurethane sealants, VT-652 is solvent-free and isocyanate-free; ensuring that the cured sealant will not shrink or have bubbling issues. It is also free of silicone oil, minimising building aesthetic issues caused by oil staining and dirt streaking problems often associated with silicone sealants.

### Applications:

Suitable for high strength sealing and bonding in construction, automotive, marine, and industrial applications. It is specially formulated for structural joint that will be subjected to dynamic stresses. Ideal for bonding of plastics, metal, rubber, wood, plywood, paperboard, leather, cloths, concrete, mortar, natural stone, tile, glass, porcelain etc.

### Applicable Test / Standard:

- 1. Low VOC - USEPA Method 24 under SCAQMD Rule 1168

Available colors: White, Black and Grey.

Item Code	Content	Carton Quantity
VT-652	290 ml Cartridge	20 / Carton



### Features

- High modulus
- High strength structural bonding
- Good UV resistance
- Paintable
- Isocyanates-free - No air bubbling
- Solvent-free - No shrinkage
- Primerless bonding to most substrates



BUS BODY CONSTRUCTION



BODY KITS BONDING



OUTDOOR PANEL BONDING



VITAL TECHNICAL SDN. BHD. (No.: 589221-K)

+603 6094 2088 (Tel) +603 6099 2930 (Fax)

sales@vitaltechnical.com

www.vitaltechnical.com



A member of

