

An ultimate D3-grade wood glue, specially formulated for woodworking applications that require resistance to short-term submersion. It offers fast setting, superior bonding strength, and versatility with various porous substrates for both indoor and outdoor use. It is non-toxic, solvent-free, and easy to clean up with water.

Applications:

Suitable for indoor and outdoor wood joining, furniture repair, wooden frames, and woodworking projects that require short-term submersion resistance. not recommended for continuous submersion or use below the waterline.







Available colour: White (Wet) Clear (Dry)

	Item Code	Content	Inner Box	Carton Quantity
	VT-768125	125 g Bottle	12	144 / Carton
	VT-768250	250 g Bottle	12	72 / Carton
1	VT-768500	500 g Bottle	_	24 / Carton
	VT-7661K	1.0 kg Bottle	-	12 / Carton
	VT-7664K	4.0 kg Pail	-	6 / Carton

Features

- Water-resistant D3
- Indoor & outdoor use
- Easy to spread
- High bond strength
- Fast curing
- Forms thin gapless layer when set
- Non-toxic, solvent free and low odour



WOOD DECK
RAILING



WOOD BONDING



WOODWORKING JOINT



VITAL TECHNICAL SDN. BHD. Co.No.: 200201021558 (589221-K)

- (Fax) +603 6094 2088 (Tel) +603 6099 2930 (Fax)
- sales@vitaltechnical.com
 - www.vitaltechnical.com











