



VT-236 V-Bond Construction Adhesive Sealant

Safety Data Sheet

according to the United Nations GHS (Rev. 9, 2021)

Issue date: 9/20/2021 Revision date: 7/23/2022 Supersedes: 9/20/2021 Version: 1.1

SECTION 1: Identification

1.1. GHS Product identifier

Product form : Mixture
Product name : VT-236 V-Bond Construction Adhesive Sealant
UN-No. (ADR) : 1133
Product group : Trade product

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Use of the substance/mixture : Sealants
Recommended use : Sealants

1.4. Supplier's details

Manufacturer

Vital Technical Sdn. Bhd.
No.93, Jalan Industri 3/3 Rawang Integrated Industrial Park,
48000 Rawang, Selangor, Malaysia.
T +603 60942088 - F +603 60992930

1.5. Emergency phone number

No additional information available

SECTION 2: Hazard identification


2.1. Classification of the substance or mixture

Classification according to the United Nations GHS

Flammable liquids, Category 2	H225	On basis of test data
Skin corrosion/irritation, Category 2	H315	Calculation method
Reproductive toxicity, Category 2	H361	Calculation method
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336	Calculation method
Specific target organ toxicity – Repeated exposure, Category 2	H373	Calculation method
Aspiration hazard Not classified		Calculation method
Hazardous to the aquatic environment – Chronic Hazard, Category 3	H412	Calculation method
Full text of H-statements: see section 16		
Adverse physicochemical, human health and environmental effects		: Highly flammable liquid and vapour, Suspected of damaging fertility or the unborn child, May cause damage to organs through prolonged or repeated exposure, May cause drowsiness or dizziness, Causes skin irritation, Harmful to aquatic life with long lasting effects.

2.2. GHS Label elements, including precautionary statements

Labelling according to the United Nations GHS

Hazard pictograms (GHS UN) : 

Signal word (GHS UN) : Danger

Hazardous ingredients : HYDROCARBONS, C7-C9, N-ALKANES, ISOALKANES, CYCLICS, NAPHTHA (PETROLEUM), HYDROTREATED LIGHT, methyl acetate

Hazard statements (GHS UN) : H225 - Highly flammable liquid and vapour
H315 - Causes skin irritation

VT-236 V-Bond Construction Adhesive Sealant

Safety Data Sheet

according to the United Nations GHS (Rev. 9, 2021)

Precautionary statements (GHS UN)	H336 - May cause drowsiness or dizziness H361 - Suspected of damaging fertility or the unborn child H373 - May cause damage to organs through prolonged or repeated exposure H412 - Harmful to aquatic life with long lasting effects : P201 - Obtain special instructions before use. P202 - Do not handle until all safety precautions have been read and understood. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 - Keep container tightly closed. P240 - Ground and bond container and receiving equipment. P241 - Use explosion-proof electrical, lighting, ventilating equipment.
-----------------------------------	---

2.3. Other hazards which do not result in classification

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to the United Nations GHS
NAPHTHA (PETROLEUM), HYDROTREATED LIGHT	CAS-No.: 64742-49-0	10 – 30	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
HYDROCARBONS, C7-C9, N-ALKANES, ISOALKANES, CYCLICS	CAS-No.: 64742-49-0	1 – 10	Flam. Liq. 2, H225 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
methyl acetate	CAS-No.: 79-20-9	1 – 10	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336

Full text of H-statements: see section 16

SECTION 4: First-aid measures

4.1. Description of necessary first-aid measures

First-aid measures general	: IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Rinse skin with water/shower. Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Irritation.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Treat symptomatically.

VT-236 V-Bond Construction Adhesive Sealant

Safety Data Sheet

according to the United Nations GHS (Rev. 9, 2021)

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media : Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media : Water spray.

5.2. Specific hazards arising from the chemical

Fire hazard : Highly flammable liquid and vapour.
Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Special protective actions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and materials for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
Other information : Dispose of materials or solid residues at an authorized site.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes.
Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.
Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

VT-236 V-Bond Construction Adhesive Sealant

Safety Data Sheet

according to the United Nations GHS (Rev. 9, 2021)

NAPHTHA (PETROLEUM), HYDROTREATED LIGHT (64742-49-0)

EU - Indicative Occupational Exposure Limit (IOEL)

Local name	Cyclohexane
IOELV TWA (mg/m ³)	700 mg/m ³
Regulatory reference	COMMISSION DIRECTIVE 2006/15/EC

USA - ACGIH - Occupational Exposure Limits

Local name	Cyclohexane
ACGIH TWA (ppm)	100 ppm
Remark (ACGIH)	TLV® Basis: CNS impair
Regulatory reference	ACGIH 2021

USA - ACGIH - Biological Exposure Indices

Local name	n-HEXANE
Biological Exposure Indices (BEI)	0.5 mg/l Parameter: 2,5-Hexanedione (without hydrolysis) - Medium: urine - Sampling time: End of shift
Regulatory reference	ACGIH 2021

methyl acetate (79-20-9)

USA - ACGIH - Occupational Exposure Limits

Local name	Methyl acetate
ACGIH TWA (ppm)	200 ppm
ACGIH STEL (ppm)	250 ppm
Remark (ACGIH)	TLV® Basis: Headache; dizziness; nausea; eye dam (degeneration of ganglion cells in the retina)
Regulatory reference	ACGIH 2021

8.2. Appropriate engineering controls

Appropriate engineering controls	: Ensure good ventilation of the work station.
Environmental exposure controls	: Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment (PPE)

Hand protection	: Protective gloves
Eye protection	: Safety glasses
Skin and body protection	: Wear suitable protective clothing
Respiratory protection	: [In case of inadequate ventilation] wear respiratory protection.
Personal protective equipment symbol(s)	



8.4. Exposure limit values for the other components

No additional information available

SECTION 9: Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	: Liquid
Colour	: Brown.

VT-236 V-Bond Construction Adhesive Sealant

Safety Data Sheet

according to the United Nations GHS (Rev. 9, 2021)

Odour	: Barely perceptible odour.
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: > 50 °C
Flammability	: Highly flammable liquid and vapour.
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: < 23 °C
Auto-ignition temperature	: Not applicable
Decomposition temperature	: Not available
pH	: Not applicable
pH solution	: Not available
Viscosity, kinematic (calculated value) (40 °C)	: 40 mm ² /s
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50 °C	: Not available
Density	: Not available
Relative density	: 1.20
Relative vapour density at 20 °C	: Not applicable
Solubility	: Not available
Particle size	: Not applicable

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable liquid and vapour.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

HYDROCARBONS, C7-C9, N-ALKANES, ISOALKANES, CYCLICS (64742-49-0)

LD50 oral rat	5840 mg/kg
LD50 dermal rat	2920 mg/kg bodyweight

VT-236 V-Bond Construction Adhesive Sealant

Safety Data Sheet

according to the United Nations GHS (Rev. 9, 2021)

methyl acetate (79-20-9)	
LD50 oral rat	≈ 6482 mg/kg
LD50 dermal rat	> 2000 mg/kg
LC50 Inhalation - Rat	> 49.2 mg/l
Skin corrosion/irritation	: Causes skin irritation. pH: Not applicable
Serious eye damage/irritation	: Not classified pH: Not applicable
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Suspected of damaging fertility or the unborn child.
STOT-single exposure	: May cause drowsiness or dizziness.
HYDROCARBONS, C7-C9, N-ALKANES, ISOALKANES, CYCLICS (64742-49-0)	
STOT-single exposure	May cause drowsiness or dizziness.
NAPHTHA (PETROLEUM), HYDROTREATED LIGHT (64742-49-0)	
STOT-single exposure	May cause drowsiness or dizziness.
methyl acetate (79-20-9)	
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: May cause damage to organs through prolonged or repeated exposure.
NAPHTHA (PETROLEUM), HYDROTREATED LIGHT (64742-49-0)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified.
VT-236 V-Bond Construction Adhesive Sealant	
Viscosity, kinematic	40 mm ² /s
HYDROCARBONS, C7-C9, N-ALKANES, ISOALKANES, CYCLICS (64742-49-0)	
Animal studies and expert judgment for classification	False
NAPHTHA (PETROLEUM), HYDROTREATED LIGHT (64742-49-0)	
Animal studies and expert judgment for classification	False
methyl acetate (79-20-9)	
Animal studies and expert judgment for classification	False

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: Harmful to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Harmful to aquatic life with long lasting effects.
Classification procedure (Hazardous to the aquatic environment, long-term (chronic))	: Calculation method

HYDROCARBONS, C7-C9, N-ALKANES, ISOALKANES, CYCLICS (64742-49-0)	
LC50 fish 1	3 – 10 mg/l
EC50 other aquatic organisms 1	4.6 – 10 mg/l

VT-236 V-Bond Construction Adhesive Sealant

Safety Data Sheet

according to the United Nations GHS (Rev. 9, 2021)

12.2. Persistence and degradability

VT-236 V-Bond Construction Adhesive Sealant

Persistence and degradability	No additional information available
-------------------------------	-------------------------------------

12.3. Bioaccumulative potential

VT-236 V-Bond Construction Adhesive Sealant

Bioaccumulative potential	No additional information available
---------------------------	-------------------------------------

12.4. Mobility in soil

VT-236 V-Bond Construction Adhesive Sealant

Mobility in soil	No additional information available
------------------	-------------------------------------

12.5. Other adverse effects

Ozone : Not classified
Other adverse effects : No additional information available




SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Additional information : Flammable vapours may accumulate in the container.

SECTION 14: Transport information

In accordance with UN RTDG / IMDG / IATA

UN RTDG	IMDG	IATA
14.1. UN number		
1133	1133	1133
14.2. UN Proper Shipping Name		
ADHESIVES	ADHESIVES	Adhesives
14.3. Transport hazard class(es)		
3	3	3
		
14.4. Packing group		
II	II	II
14.5. Environmental hazards		
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No
No supplementary information available		

VT-236 V-Bond Construction Adhesive Sealant

Safety Data Sheet

according to the United Nations GHS (Rev. 9, 2021)

14.6. Special precautions for user

UN RTDG

Limited quantities (UN RTDG) : 5L
Excepted quantities (UN RTDG) : E2
Packing instruction (UN RTDG) : P001, IBC02
Special packing provisions (UN RTDG) : PP1
Portable tank and bulk container special instructions (UN RTDG) : T4
Portable tank and bulk container special provisions (UN RTDG) : TP1, TP8

IMDG

Limited quantities (IMDG) : 5 L
Excepted quantities (IMDG) : E2
Packing instructions (IMDG) : P001
Special packing provisions (IMDG) : PP1
IBC packing instructions (IMDG) : IBC02
Tank instructions (IMDG) : T4
Tank special provisions (IMDG) : TP1, TP8
EmS-No. (Fire) : F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS
EmS-No. (Spillage) : S-D - SPILLAGE SCHEDULE Delta - FLAMMABLE LIQUIDS
Stowage category (IMDG) : B
Properties and observations (IMDG) : Adhesives are solutions of gums, resins, etc., usually volatile due to the solvents. Miscibility with water depends upon their composition.

IATA

PCA Excepted quantities (IATA) : E2
PCA Limited quantities (IATA) : Y341
PCA limited quantity max net quantity (IATA) : 1L
PCA packing instructions (IATA) : 353
PCA max net quantity (IATA) : 5L
CAO packing instructions (IATA) : 364
CAO max net quantity (IATA) : 60L
Special provisions (IATA) : A3
ERG code (IATA) : 3L

14.7. Transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations specific for the product in question

No additional information available

SECTION 16: Other information

Issue date : 20/09/2021
Revision date : 23/07/2022
Supersedes : 20/09/2021

Full text of H-statements:

H225	Highly flammable liquid and vapour
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H317	May cause an allergic skin reaction

VT-236 V-Bond Construction Adhesive Sealant

Safety Data Sheet

according to the United Nations GHS (Rev. 9, 2021)

Full text of H-statements:	
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H361	Suspected of damaging fertility or the unborn child
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

Safety Data Sheet (SDS), UN

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.